

Colour Laser Multifunction Printer

Usability, Full-functionality, Creativity

To serve your creativity, CM1100 series are designed to be compact printers with easy-to-use functions for not only printing out your masterpieces but also digitalizing your brilliant work results. Complete your daily printing, copying and scanning tasks with our excellently-designed products.



COLOR

PRECISE AND PROFESSIONAL



SimpleStart with One-step
Driver Installation



StrongBackup with High Processor
Speed and Memory



User-friendly

Auto Duplex Printing for Your Convenience



Diverse

Choices on Consumables for Your Needs

Model	CM1100DN		CM1100DW	CM1100ADN	CM1100ADW	
Function Connectivity	Print / 0 USB + NET	Copy / Sc	an (FB) USB + NET + WI-FI	Print / USB + NET	Copy / Scan (FB+ADF) USB + NET + WI-FI	
PRINT SPECIFICATION	<u> </u>					
Print speed (A4/LTR)	18ppm (A4) / 19ppm (LTR)					
Duplex print speed	6ppm (A4) / 6ppm (LTR)					
First print out time	Mono: 10s; Colour: 11s					
Printer language	PCL6/PS3					
Processor speed	1.0 GHz					
Memory	1.0 GB					
Maximum monthly duty cycle	30,000 Pages					
Recommended monthly volume	300-1,500 Pages					
Control panel	2-line LCD 3.5-inch touch screen					
Duplex printing	Auto					
Mobile print	AirPrint; Mopria; Pantum APP					
Standard ports	USB2.0 (High Speed) IEEE802.3 10/100Base-Tx	I	USB2.0 (High Speed) IEEE802.3 10/100Base-Tx IEEE802.11b/g/n (support WPS)	USB2.0 (High Speed) IEEE802.3 10/100Base-Tx	USB2.0 (High Speed) IEEE802.3 10/100Base-Tx IEEE802.11b/g/n (support WPS)	
Direct USB		/			Yes	
Other printer function PAPER HANDLING	Watermark Printing; Poster Printing; Multi-page in One Printing; Brochure Printing; One-step Driver Installation					
Paper input capacity	250 Pages					
Multipurpose tray	1 Page					
Paper output capacity	100 Pages					
Media types	Plain: 70~105g/m² (Including 105g/m²); Thin: 60~70g/m² (Not including 70g/m²); Thick: 105~200g/m² (Not including 105g/m²); Transparency/Cardstock/Label/Envelope					
Media sizes	A4, Letter, Legal, Folio, Oficio, JIS B5, ISO B5, Executive, Statement, A5, big 16K, 16K, big 32K, 32K, A6, No.10 Env, Monarch Env, DL Env (Envelope No.5), C5 Env (Envelope No.7), C6 Env, Yougata4, Younaga3, Nagagata3, Yougata2, ZL (Envelope No.6), Postcard, B6, Japanese Postcard Custom: minimum 96x148 mm-maximum 216x356 mm					
Media weights	Standard tray: 60~200g/m²; Multipurpose tray: 60~105g/m²					
COPY SPECIFICATION						
Copy colour	Colour/black					
Copy speed			18p	ppm		
First copy out time		Fb:16s			b:16s ADF:18s	
Max. copy page	99 Pages					
Copy reduce / enlarge settings	25% - 400%					
SCAN SPECIFICATION	ID copy; Receipt copy; N-up copy; Clone copy; Poster copy					
Scanner type		FB			FB+ADF	
Scan technology	CIS					
Scan mode	Color, Gray, Monochrome (PC only)					
Scan to	PC/Email/FTP	ı	PC/Email/FTP/iOS/Android	PC/Email/FTP/ USB flash disk	<u> </u>	
ADF capacity		/			50 Pages	
Scan to USB	1				Yes	
Colour scanning	Yes					
Format GENERAL	JPEG, TIFF, PDF					
Printer dimensions (W×D×H)	401*411*314 mm				01*411*358 mm	
Weight (with cartridge)	18.5 k			<u> </u>	19.4 kg	
Package dimensions (W×D×H)	535*	555*412	mm	5	35*555*456 mm	
Total weight (Including printer, ca	rtridge and package) 21.2 kg			22.1 kg		
Noise Level			Print/scan≤52 dB (A); Copy≤54 dB (A); Mute≤47 dB (A); Standby≤30 dB	(A)	
Power consumption	Print Average: ≤380W; Standby: ≤10W; Dormant: ≤1W; Off: ≤0.15W					
Power	AC 110-127V, 50Hz/60Hz, 7A; AC 220-240V, 50Hz/60Hz, 3.5A					
Print environment	Operating temperature: 10-32°C; Relative humidity: 20% ~ 80%RH; Altitude: ≤2,000m					
Operating system compatibility	Microsoft Windows XP/Windows 7/Windows 8.1/Windows 10/Windows 11/Windows server/2012/2016 Mac OS 10.9∼12 Linux Ubuntu 16.04&18.04&20.04&22.04					
CONSUMABLE Consumable type	One-piece					
Starter cartridge*	One-piece CTL-1100K: 1,000 Pages; CTL-1100C/CTL-1100M/CTL-1100Y: 700 Pages					
Cartridge model and yield*	①CTL-1100K: 1,000 Pages; CTL-1100C/CTL-1100M/CTL-1100Y: 700 Pages ② CTL-1100HK: 2,000 Pages; CTL-1100HC/CTL-1100HM/CTL-1100HY: 1,500 Pages ③ CTL-1100X: 3,000 Pages; CTL-1100XC/CTL-1100XM/CTL-1100XY: 2,300 Pages					
Waste powder bottle*	CWT-1100:15,000 Pages					

Notes: (1) The toner cartridge capacity is the average print volume of it during continuous printing at the single-sided mode, based on the ISO/IEC 19798 standard.
(2) All the specifications are from Pantum internal test data. Actual print volume may vary based on other factors such as paper size and feed direction, toner coverage, tray source, percentage of black-only printing, and average print job complexity.